



Our popular Cavalier just got better!

The high-pressure Class H fire hose boasts an improved abrasion resistance by 50%. Cavalier's tough exterior gives the textile reinforcement extra protection and helps keep it clean.

Used to protect many commercial and industrial sites, it can be used for high-pressure wash-down applications.

Cavalier is easy to roll up after use and takes up little space in a fire cabinet. Lined with thermoplastic polyurethane, Cavalier is manufactured in our ISO 9001:2015 quality-certified factory and can be fitted to a wide range of couplings.











- ✓ Coated fire hose
- √ Working pressure 2100 kPa
- √ Mildew resistant
- √ No need for drying after use
- √ Standard red: other colours to order
- √ Australian Made

## **TECHNICAL DATA**

Diameter (ID)	25 mm	38 mm	51 mm	64 mm
	1"	1.5"	2"	2.5"
Max. working pressure*	2100 kPa	2100 kPa	2100 kPa	2100 kPa
Min. burst pressure	5250 kPa	5250 kPa	5250 kPa	5250 kPa
Weight/m	0.17 kg	0.25 kg	0.34 kg	0.38 kg
30 m coil diameter	0.41 m	0.43 m	0.44 m	0.44 m
Part #	HHV025XRA	HHV038XRA	HHV051XRA	HHV064XRA

<sup>\*</sup>Dependent on maximum working pressure of attached couplings if lower.

NOTE: For larger diameters, refer to Centurion or Rapier



Scan here to learn more

## **Crusader Hose Pty Ltd**

22 Industry Place, Bayswater VIC 3153 Australia

e: sales@crusaderhose.com.au p: +61 3 9720 1100

Contact Crusader Hose to ensure that the current technical data sheets and documentation are used.



Crusader Hose reserves the right to modify any specification as

part of ongoing product development and without prior notice.



