

Flexiline™

Industrial layflat hose

12
MONTH
WARRANTY



IDEAL FOR

- Industrial pumping
- Dewatering hose

Flexiline is a flexible layflat hose used for industrial pumping applications. It is robust and typically used for pumping pressures operating up to 1500 kPa. It can be supplied with a large range of couplings, including Bauer, for quick-connect dewatering use.

Lengths up to 20 m can be easily handled. However, for longer lengths, we recommend our reel systems; this makes the handling safe, quick and easy.

The polyurethane cover ensures maximum abrasion resistance and the textile reinforcement gives burst strength. **Flexiline** is available in 102 mm, 152 mm and 203 mm diameters. All hose is fully tested and a fitted assembly can be supplied with test certification.

FEATURES

- ✓ Tough polyurethane cover
- ✓ Low coil volume for easy handling
- ✓ Suitable with many couplings: Bauer, Camlock & Flange
- ✓ 12-month warranty
- ✓ Australian Made

TECHNICAL DATA

Diameter (ID)	102 mm	152 mm	203 mm
	4"	6"	8"
Max. working pressure*	1500 kPa	1500 kPa	1500 kPa
Min. burst pressure	3000 kPa	3000 kPa	3000 kPa
Tensile load	8 t	14 t	18 t
Weight/m	1.5 kg	2.1 kg	2.8 kg
Avg. single wall thickness	3.2 mm	3.7 mm	4.0 mm
Part #	HNF102XBA	HNF152XBA	HNF203XBA

*Dependent on maximum working pressure of attached couplings if lower.



Scan here to learn more

Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia

e: sales@crusaderhose.com.au p: +61 3 9720 1100

www.crusaderhose.com.au

2411

Crusader Hose reserves the right to modify any specification as part of ongoing product development and without prior notice.

Contact Crusader Hose to ensure that the current technical data sheets and documentation are used.

